

Sprinkler System Wire

18 AWG, Multi-Conductor



Made to Your Specifications

30 Volts

60°C

APPLICATIONS

Cerrowire Sprinkler System Wire is 18 AWG made to customer specifications with 4, 5, 7, or 10 conductors, suitable for direct burial on applications up to 30 volts, including field and central controls for underground sprinkler systems. 50', 100' and 500' lengths.

ASSEMBLY

6 to 10 soft bare copper conductors (to order) are twisted without fillers to a LHL. Insulation is 0.016" nominal-wall SR-PVC, and jacket is 0.025" nominal-wall black polyethylene with a parallel ripcord. 4- and 5-conductor constructions are parallel.

INDUSTRY STANDARDS/CERTIFICATIONS

UL® Direct Burial Sprinkler Systems Wire
C(UL) Lawn Sprinkler Systems Wire
EU RoHS Directive

SURFACE PRINT

Sample: E107861 (01-12345) 18 AWG 30 V DIRECT BURIAL SPRINKLER SYSTEMS WIRE
(UL) E323899 30 V DIR BUR LSS C(UL) (MM/YY) RoHS

©2010, Cerro Wire LLC
All Rights Reserved



MADE IN THE USA

cerrowire®

Electrical Division: 800.523.3869 | FAX 877.877.9563
Consumer Markets Division: 866.572.3776 | FAX 812.793.2626
www.cerrowire.com

A Marmon Wire & Cable/
Berkshire Hathaway Company

Sprinkler System Wire 18 AWG, Multi-Conductor

PART NUMBER	NO. OF COND.	AWG SIZE	LENGTH OF CORD (FT.)	PACKAGE TYPE	POWER RATING			PKG. PER CTN.	APPROX. WEIGHT PER CTN. (LBS) ^(S)	CARTON DIMENSIONS (HxWxD)	UPC NUMBER
					VOLTS	AMPS	WATTS				
240-1004J	4	18	500	Reel Wrap	30	4	120	1	13.75	6.5 x 12 x 12	048243465729
240-1005B	5	18	50	Shrink Bundle	30	4	120	10	17.15	8.5 x 8.25 x 19	048243465798
240-1005C	5	18	100	Shrink Bundle	30	4	120	6	20.50	10.25 x 9.88 x 14.75	048243465828
240-1005J	5	18	500	Reel Wrap	30	4	120	1	17.15	6.5 x 12 x 12	048243465835
240-1007B	7	18	50	Shrink Bundle	30	3.5	105	10	24.05	8.5 x 8.25 x 19	048243465996
240-1007C	7	18	100	Shrink Bundle	30	3.5	105	6	28.86	9.75 x 9.75 x 14.25	048243466023
240-1007J	7	18	500	Reel Wrap	30	3.5	105	1	24.03	6.5 x 12 x 12	048243466030
240-1010J	10	18	500	Reel Wrap	30	3.5	105	1	37.50	12 x 12 x 12	048243466337

^(S) Actual shipping weight may vary.

Color Code

NO. OF CONDUCTORS	COLOR
1	RED
2	WHITE
3	DARK BLUE
4	GREEN
5	BROWN
6	BLACK
7	YELLOW
8	ORANGE
9	VIOLET
10	GRAY