


# Cabled THHN/THWN

Vynylon® PVC/Nylon



**90°C Dry / 75°C Wet**

**600 Volts**

**Gasoline and Oil  
Resistant**

## APPLICATIONS

600-volt black, white & green building wire for use in commercial and industrial applications as specified in the NEC®, including machine-tool and appliance wiring. Marked VW-1. Our 3 most popular THHN conductors are now available in one convenient retail package

## CONDUCTORS

Solid conductors: Uncoated copper per ASTM-B3.  
Stranded conductors: Uncoated copper per ASTM-B3, ASTM-B787

## INSULATION

Color-coded, heat- and moisture-resistant PVC (polyvinyl chloride)

## JACKET

Nylon (polyamide), clear

## INDUSTRY STANDARDS

UL 83: File No. E15119  
UL 1063 (MTW): File No. E85964  
AWM: File No. E11829  
Canada Standard C22.2 No. 75 and CSA Bulletin No. 1451  
ASTM Standards: B3, B8, B787  
WC70/ICEA S-95-658  
Federal Specification A-A-59544  
NFPA-70: National Electrical Code®

## SURFACE PRINT

Sample: CERROWIRE VINYLON-A 14 AWG (2.08 mm 2) (UL) THHN or THWN or MTW or AWM GR2 VW-1 600V - C(UL) TWN75 or T90 NYLON

©2010, Cerro Wire LLC  
All Rights Reserved



LISTED



MADE IN THE USA

**cerro**  
Electrical®

866.572.3776 | FAX 812.793.2626  
www.cerrowire.com

## Cabled THHN/THWN

Vinylon® PVC/Nylon

PRODUCT CODE	CONDUCTORS		COVERING		APPROX. COND. O.D. INCHES	APPROX. CABLE O.D. INCHES	ALLOWABLE AMPACITIES			APPROX. CNET. WT. LBS./ 100 FT.
	AWG SIZE	NO. OF STRANDS	PVC INS. MILS.	NYLON JKT. MILS.			60°C **	75°C ***	90°C ****	
112-141253B	14	SOLID	15	4	0.104	0.210	15	15	15	4.5
112-141253C	14	SOLID	15	4	0.104	0.210	15	15	15	4.5
112-341253B	14	STRANDED	15	4	0.104	0.210	15	15	15	4.5
112-341253C	14	STRANDED	15	4	0.104	0.210	15	15	15	4.5
112-161253B	12	SOLID	15	4	0.120	0.235	20	20	20	6.9
112-161253C	12	SOLID	15	4	0.120	0.235	20	20	20	6.9
112-361253B	12	STRANDED	15	4	0.120	0.235	20	20	20	6.9
112-361253C	12	STRANDED	15	4	0.120	0.235	20	20	20	6.9