

Sound and Security Wire

Shielded Riser Cable
Security, Intercom, and Audio



18 & 22 AWG

300 Volts

S-R PVC Insulated

-10 °C to +75 °C

APPLICATIONS

Intercom/PA systems, Sound/Audio systems.

CONDUCTORS

18 & 22 AWG 7 strand bare copper.

ASSEMBLY

18 & 22 AWG conductors cabled together with a 2" nominal left-hand lay. Nylon rip cord for ease of jacket stripping.

INSULATION

SR-PVC .060 in O.D.

JACKET

0.014" nominal wall gray flame-retardant polyvinyl chloride (PVC).

INDUSTRY STANDARDS/CERTIFICATIONS

UL Listed Type CL3R/FPLR.CMR
C(UL) CMR
NEC Article 725, 760 and 800
UL 1666 Riser Flame Test
RoHS Directive
California State Fire Marshal Approved

SURFACE PRINT

Sample: E111272 (01-12345) 22 AWG SHIELDED CL3R/FPLR (UL) OR CMR C(UL)US
(MM/YY) RoHS 000002FT

©2010, Cerro Wire LLC
All Rights Reserved



MADE IN THE USA

cerro
Electrical®

866.572.3776 | FAX 812.793.2626
www.cerroretail.com

18 & 22 AWG Sound and Security Wire Shielded Riser Cable Security, Intercom, and Audio

CERRO FINISHED GOODS PART #	DESCRIPTION	PUT-UP	PACKAGE TYPE	SPOOLS/COILS PER MASTER CARTON	SHIPPING WEIGHT PER MASTER CARTON	UPC CODE
225-0022J	22-2 STRD Overall Shield Sec Cable-500 ft	500	REEL Sleeving	2	7.4000	048243315918
225-0024J2	22-4 STRD Overall Shield Sec Cable-500 ft	500	REEL Sleeving	2	12.9000	048243315963
225-1004J	18-4 STRD Overall Shield Sec Cable-500 ft	500	REEL Wrap	1	19.9500	048243315765
225-1002J2	18-2 STRD Overall Shield Sec Cable-500 ft	500	REEL Sleeving	2	20.3000	048243315710