

**NEW,
IMPROVED**
slip technology!

XHHW-2

XHHW-2

600V/1000V
90°C Wet or Dry
Sunlight Resistant

Description:

Thermoset-insulated copper wire with SLiPWire™ Technology (8 AWG and larger) for fast and easy pulling in conduit. This 90°C building wire is for use in residential, commercial and industrial applications. Intended for use in accordance with the National Electrical Code® in both wet and dry locations and rated at both 600 volts and 1000 volts. Conductors 1/0 AWG and larger are rated for use in cable tray. Sunlight resistant in black for all sizes, and in all colors for sizes 8 AWG and larger. Good choice for industrial applications where better insulation resistance to moisture and heat are desired. Rated as Gas and Oil Resistant II.

Materials:

Stranded conductors: Uncoated, soft copper per ASTM B3 and ASTM B8
Insulation: Crosslinked polyethylene with SLiPWire™ Self-Lubricating Polymer Technology (sizes 8 AWG and larger). Printed with True Sequential Footage™.



Standards:

UL 44: 125474
ASTM B3
ASTM B8
Federal Specification A-A-59544
NFPA 70 (National Electrical Code)
NEMA WC 70 Construction
Requirements
RoHS/REACH Compliant

Surface Print:

Sample: Cerrowire-U SLiPWire™
250 KCMIL (UL) XHHW-2 GR11 FOR
CT USE SR 600V XL
(Additional information may be included, markings vary by size.)

Conductors	Insulation Thickness (mils)	Approx. O.D. (inches)	Net Weight Lbs/MFt
14 SOL	30	0.123	18
12 SOL	30	0.140	26
10 SOL	30	0.160	38
14 STR	30	0.128	18
12 STR	30	0.146	26
10 STR	30	0.169	38
8	45	0.233	63
6	45	0.272	95
4	45	0.318	145
3	45	0.346	180
2	45	0.377	223
1	45	0.433	281
1/0	55	0.471	348
2/0	55	0.515	434
3/0	55	0.564	541
4/0	55	0.620	674
250	65	0.685	813
300	65	0.735	973
350	65	0.784	1121
400	65	0.831	1280
500	65	0.915	1587
600	80	1.040	1919
750	80	1.143	2417
1000	80	1.292	3250

Available colors:

- Black
- White
- Red
- Orange
- Yellow
- Green
- Blue
- Brown
- Grey

Features:

SLiPWire™
technology

TRUE Sequential Footage™

cerrowire
MaxPrint®

RoHS
compliant



Data are approximate and subject to normal manufacturing tolerances. Strand counts may vary for SIW constructions. It is the sole responsibility of the end user to determine suitability of this product for its intended use and application. Most colors available on all sizes; call Cerrowire to verify. Other colors may be available upon request.

cerrowire®
cerrowire.com

Retail Distribution 866.572.3776
Electrical Distribution 800.523.3869

